

# DEVOLD® TOTAL

## FLAME RETARDANT WOOL / LENZING BLEND

DEVOLD® TOTAL gir god beskyttelse mot kulde og flammer. Plaggene er ribbstrikket i 50 % ull og 50 % Lenzing FR®, som er en flammehemmende fiber. Devold® Total er flammehemmende og smelter ikke. Undertøyet har god passform og tørker på kroppen. Devold® Total er undertøy for ansatte i brannvesenet, e-verk, offshore og industri. Devold® Total er Super Wash behandlet for å hindre krymp.



TOTAL t-shirt - GP 109 210 A 290A

MATERIAL	50% Wool (Merino) / 50 % Lenzing FR®
STRUCTURE	Rib
WEIGHT	220 g/m² +/-10%
SPECIAL TREATMENT	Preshrunk (Super Wash)

Lenzing FR®



TEST	RESULT	REQUIREMENT
① Limited flame spread: EN 15025-A1-A2	Pass	Pass
② Convective heat: EN 9151	B1	B1
③ Radiant heat: EN 6942	C1	C1

ARC RESISTANCE TEST: EN 61482-2

### TEST FOR FLAME RETARDANT PROPERTIES

EN ISO 11612: Standard describing requirements for protective clothing for workers exposed to heat and flame. Test descriptions and certificates at [www.devold.com](http://www.devold.com).